



Danish Oil

PRODUCT DATA

Description

A blend of resins and wood/tung oil to give a protective natural finishes to work tops and previously untreated furniture, including doors.

Area of use

Interior

Substrates

Wood

Packing

500ml and 5 litres

Physical Constants

Colour:	Pale Amber
Finish:	Satin
Volume solids:	35%
Theoretical spreading rate:	18 – 20 sq.meters per litre
Flash point:	42°C
Specific gravity:	0.90
Dry to touch:	4 – 8 hours (depending on conditions)
Overcoating time:	18 – 24 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush
Thinner:	N/A
Cleaning of tools:	White Spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.