



Doorstep Paint

PRODUCT DATA

Description

Blend of Polyurethane and durable resins designed to colour, protect and rejuvenate dowdy looking steps. No primer required. Suitable application onto most surfaces and will provide a slip resistant, hard wearing finish.

Sealing/Priming

It is only necessary to seal a porous substrate such as new or bare concrete. A sealer coat is achieved by adding 10% white spirit to the paint. Please note new concrete surfaces can only be painted after 6-8 weeks.

Area of use

Interior and Exterior

Substrates

Brick, Concrete and Wood

Packing

500ml (Toolstation only)

Physical Constants

Colours:	Tile Red-04C39 and Black
Finish:	Semi Gloss
Volume solids:	44%
Theoretical spreading rate:	6 – 7 sq. metres per 500ml (depending on surface)
Flash point:	42°C
Specific gravity:	1.10 - 1.20
Dry to touch:	2 - 4 hours (20°C)
Over-coating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush
Thinner:	White Spirit
Cleaning of tools:	White Spirit
<u>Surface condition</u>	The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.
Please check colour before use. If using multiple cans please check batch numbers are the same.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.