



F-Scuff

PRODUCT DATA

Description

A high-performance, single component water-based paint specifically designed to deliver outstanding performance, durability, and protection for the toughest high-traffic areas in busy commercial areas. This product offers superior scuff resistance in an easy to use, low odour formulation. This product provides a high-quality appearance with reduced maintenance. The beautiful low sheen finish is perfect for corridors, fitting rooms and waiting areas.

Area of use

Ideal for high-traffic areas, for use on primed or previously painted plaster type substrates, wood, metal and wallpapered surfaces.

Substrates

Doors, skirting boards, general timber and suitably painted metals.

Packing

2.5lts

Physical Constants

Colour:	White
Finish:	Low Sheen
Volume solids:	38%
Theoretical spreading rate:	12 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.2
Dry to touch:	30 minutes
Over-coating time:	4 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, roller, conventional and airless spray
Thinner:	Water
Cleaning of tools:	Water

Surface Condition

Surface should be clean, dry and free of dust, dirt and other contamination. Remove any loose and defective paint. Mould, lichen and algae should be removed with a suitable treatment prior to application.

*Please refer to the Material Safety Data Sheet for further information.
Please check colour before use. If using multiple cans please check batch numbers are the same.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.