



## Asipo Fine Textured Masonry Paint

### PRODUCT DATA

---

#### Description

A superior water-based decorative coating. Provides protection against surface contamination and discolouration. An economic solution with long-term protection against mould and algae. Easy to apply with a fine textured flexible finish.

#### Sealing/Primer

On new render or masonry service a sealant coat is recommended, this can be achieved by thinning the paint by 10% with water.

#### Area of use

Exterior

#### Substrates

Masonry

#### Packing

5 litres (min batch 200L)

#### Physical Constants

Colours: White or Magnolia (special colours on request)

Finish: Matt

Volume solids: 55%

Theoretical spreading rate: 8-10 sq. metres per litre

Flash point: N/A

Specific gravity: 1.65

Dry to touch: 2 hours (20°C)

Overcoating time: 4 - 6 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details

Application method: Brush or roller

Thinner: Water

Cleaning of tools: Water

#### Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information. For additional guidance please contact your local Technical Sales Representative. Please check colour before use. If using multiple cans please check batch numbers are the same.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.