Kitchen & Bathroom Paint



PRODUCT DATA

Description

Kitchen & Bathroom Paint is a superior water-based decorative emulsion that provides an extra durable washable finish for areas that are periodically subjected to humidity and condensation. Humidity and condensation can lead to the growth of mould and algae. Kitchen & Bathroom Paint is an easy to apply product that ensures long-term protection from mould and algae.

Sealing/Primer

On new plaster a sealant coat is recommended, this can be achieved by thinning the paint by 10% with water.

Area of use

Internal wall and ceiling areas

Substrates

Masonry and plaster

Packing

2.5 litres

Physical Constants

Colours: White and Magnolia

Finish: Matt

Volume solids: 48%

Theoretical spreading rate: 12 sq. metres per litre

Flash point: N/A

1.25 - 1.4Specific gravity:

Dry to touch: 2 hours (20°C)

Overcoating time: 4 hours

*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.

Application Details

Brush or roller

Application method: Thinner: Water Cleaning of tools:

Surface condition The surface should be stable, firm, dry and free of dust sand, loose

old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

Please refer to the Material Safety Data Sheet for further information. For additional guidance please contact your local Technical Sales Representative.

Please check colour before use. If using multiple cans please check batch numbers are the same.