



Special Pale Polish

PRODUCT DATA

Description

A high quality polish made from the finest bleached dewaxed shellac. Most suitable for finishing items such as inlay and marquetry in view of its clarity of film.

Area of use

Interior

Substrates

Wood

Packing

500ml and 5 litres

Physical Constants

Colour:	Transparent
Finish:	Gloss
Volume solids:	25%
Theoretical spreading rate:	18 sq. metres per litre
Flash point:	18°C
Specific gravity:	0.87
Dry to touch:	5 -10 minutes (20°C)
Over-coating time:	15 minutes

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Cloth or Pad
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, dirt, grease and oil. Use a shellac sanding sealer prior to using Special Pale Polish

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.